

N75HP429-1631

Product Specification For Inductive Differential Mode Nanotech® Cores



MH&W International Corp.

575 Corporate Drive, Suite 4200, Mahwah, NJ 07430 USA

Phone 201-252-8125 Email: sales@mhw-intl.com

Mechanical Specification

Bare Core Dimensions:

3.94 x 3.15 x 1.18 inch
(100 x 80 x 30 mm)

le: 28.16 cm

Ae: 2.25 cm²

Weight: 1.1 lbs (500 grams)

Packing: 4 pc/layer, 3 layers/box

Box Quantity: 12 pieces


Core Material: Nanocrystalline

Currie Temp: 1,112°F (600 °C)

RTI Temp (0.81): 248°F (120°C)

Marking:

N75HP429-1631



Dimensions = inches (mm)

Electrical Core Performance

Permeability @ frequency = 10 KHz and Hpeak = 3.0 mA/cm ~ 60,000

| Inspection Value | Measured Value | Measurement Limits | Frequency | L _{eff} * N (mA*turn) |
|------------------|-------------------------------------|--------------------|-----------|--------------------------------|
| | A _L (μH/N ²) | 42.4 - 84.3 | 10 KHz | 50 |
| | A _L (μH/N ²) | 14.5 min | 100 KHz | 50 |

*Saturation Current (Isat) of nanocrystalline material: Peak value of the exiting current when the initial inductance level is dropped to 10 per cent. Saturation behaviour is dependant on frequency, signal shape and leakage field. The current value is a calculated value for design help only and cannot be guaranteed. Isat is calculated @ B = 1.0 T - μnom - N = 1.

Core Finishing

| | | | | | | |
|--------------------|--------------|-----------------------------|---------------|--------------|---------------|-------------|
| Type: | Plastic Case | Case Material Alternatives: | Zytel FR70G25 | Rynite FR530 | Longlite 4130 | PA66-R11G25 |
| Voltage Breakdown: | 2,500 VRMS | Case UL file Number: | E41938 | E41938 | E59481 | E484599 |

Certification

MH&W International certifies that the manufacturing and the quality process meet all requirements of IEC Part 1: General Specification for "Fixed Inductors For Electromagnetic Interference Suppression", IEC 60938-1:1999 + A1:2006. This International Standard is used in lieu of requirements/documents pertaining to UL, CE, CSA, DIN and other individual agencies. The flame insulation rating meets UL-94V-0.

MH&W International certifies the product described herein is in compliance with the Directive 2011/65/EU of the European Parliament and of the council of 8 June, 2011 on the Restriction of the use of Certain Hazardous Substances in Electrical and Electronic Equipment (RoHS2 Directive).

| Rev # | Date | Description | Drawing Approval | Drawing Number |
|-------|----------|----------------------------------|-------------------------|------------------|
| 2 | 08/17/17 | Initial Issue | Engineering: D. Rollins | N75HP429-1631 R3 |
| 3 | 04/05/21 | Updated to new datasheet format. | Sales: B. Wilson | |